


NORDIC ID UHF RFID READER NUR-05WL2



NUR-05WL2 is a compact UHF RFID reader/writer module. Its small footprint, SMD, low power consumption and high RF output makes it an outstanding choice for everything from simple mobile readers to port readers with multiple antennas.

NUR-05WL2 is compatible with the EPC C1G2 (ISO18000-6C) standard. The module meets the requirements of ETSI, FCC and IC radio regulations. NUR-05WL2 is also compatible with the DRM (dense reader mode) requirements.

PRODUCT HIGHLIGHTS

- SMD module with minimal footprint
- High performance with +27dBm output power, adjustable in 1dB steps
- Low power consumption
- UART and USB 2.0 communication
- Autosensing inventory parameter possibility
- 5 programmable GPIO with event trigger
- Selectable receiver decoding, link frequency and transmitter modulation (ASK/PR-ASK)
- Increased sensitivity due to automatic leakage cancellation

SOFTWARE DEVELOPMENT

- Ready-to-use Nordic ID NUR API that provides full control over the module
- Application can be written in C/C++ and .NET languages

APPLICATION

- Item / pallet / container level tracking
- Inventory
- Counterfeiting
- Brand protection

All information is subject to change without prior notice.

UHF RFID	
RF Power	+27 dBm (500 mW) adjustable in 1 dB steps
Typical reading speed	200 tags / sec
RFID Protocol support	EPC class 1 gen2 (ISO 18000-6C)
Frequency	ETSI 865.6 – 867.6 MHz FCC / IC 902 – 928 MHz Built-in region support for Japan, Malaysia, China, Brazil, New Zealand and Australia. Others can be customized via NUR API
Regulatory	CE ETSI EN 302 208 CE ETSI EN 301 489 FCC part 15.247 IC RSS-210 Safety IEC 60950-1
SIZE AND WEIGHT	
Dimensions	W 25.4 x L 22 x H 2.5 mm (W 1 x L 0.87 x H 0.1 inch)
Weight	2.5 g (0.09 oz)
INTERFACE	
Communication interface	USB 2.0 full speed UART
Antenna	50 Ω / VSWR <1.5:1
GPIO	5 pcs / 3.3 V
POWER	
Operating Power	2.6 W (max)
Supply Voltage	3.3 to 5.5 VDC (typical 3.6 VDC)
ENVIRONMENT	
Operating Temperature	-20 °C to 55 °C (-4 to 130 °F)
Storage Temperature	-40 °C to 85 °C (-40 to 185 °F)

NORDIC ID HEADQUARTERS
Myllyojankatu 2 A
FI-24100 Salo
FINLAND
tel. +358 2 727 7700
fax +358 2 727 7720
info@nordicid.com
www.nordicid.com

UNITED KINGDOM
Nordic ID Ltd
Stratford-upon-Avon, UK
tel. +44 1789 294 799
fax +44 1789 294 739
sales@nordicid.co.uk
www.nordicid.com

GERMANY
Nordic ID GmbH
Bielefeld, Germany
tel. +49 521/557717-0
fax +49 521/557717-10
info@nordicid.de
www.nordicid.de

BENELUX
Alphen aan den Rijn
The Netherlands
tel. +31 172 233 097
fax +31 172 475 653
info@nordicid.nl
www.nordicid.nl

V1001



EU DIRECTIVE
2002/96/EC ON WASTE
ELECTRICAL AND
ELECTRONIC
EQUIPMENT (WEEE)

